

This listing of the claims will replace all prior versions, and listings, of claims in the patent application.

Listing of Claims:

Claims 1-3 (Cancelled)

1 Claim 4 (Original) A permanently attached hose coupling, for a pressurized conduit end,
2 having a generally tubular nipple and a generally cylindrical shell permanently attached
3 to said nipple and generally surrounding said conduit end, said nipple having a
4 longitudinal axis, a first end, a second end, a plurality of circumferential grooves located
5 between said first and said second ends, a bore extending from said first end to said
6 second end, and an insert portion adjacent said plurality of grooves inserted into said
7 conduit end;

8 wherein said grooves are dimensioned for affixedly receiving at least one
9 of an inside surface, an end surface and an outside surface of said generally cylindrical
10 shell; and

11 said grooves comprising:

12 a first groove with a generally flat base portion parallel with said
13 longitudinal axis, a first substantially vertically oriented side wall, and a second
14 substantially vertically oriented side wall having a maximum radial extent less than said
15 first side wall; a second groove adjacent said first groove, with a generally flat base
16 portion parallel with said longitudinal axis having a diameter less than said first groove
17 base portion, a first substantially vertically oriented side wall having a maximum radial
18 extent similar to said first groove second side wall, and a second substantially vertically
19 oriented side wall having a maximum radial extent less than said second groove first side
20 wall; and

21 a third groove adjacent said second groove, with a generally flat base
22 portion parallel with said longitudinal axis having a diameter less than said second

23 groove base portion, a first substantially vertically oriented side wall having a maximum
24 radial extent similar to said second groove second side wall and a second substantially
25 vertically oriented side wall having a maximum radial extent greater than said third
26 groove first side wall.

1 Claim 5 (Original) The hose coupling as in claim 4 wherein said first groove second side
2 wall and said second groove second side wall have a contoured top portion.

1 Claim 6 (Original) The hose coupling as in claim 4 wherein said first groove second side
2 wall and said second groove second side wall have an angled top portion.

1 Claim 7 (Original) The hose coupling as in claim 4 wherein said insert portion has a
2 plurality of spaced, circumferentially extending, frusto-conically shaped protrusions on
3 the outer surface thereof.

1 Claim 8 (Original) The hose coupling as in claim 7 wherein one of said plurality of
2 spaced protrusions is positioned approximately equidistant between said third groove and
3 said second end and has a maximum radial extent greater than that of each of the others
4 of said plurality of protrusions.

1 Claim 9 (Original) The hose coupling as in claim 4 wherein said generally flat base
2 portion of each of said plurality of circumferential grooves has a series of surface
3 disruptions along its circumference.

1 Claim 10 (Original) The hose coupling as in claim 4 wherein the outer surface of said
2 third groove second substantially vertically oriented side wall has threads for attachment
3 with said generally cylindrical shell.

1 Claim 11 (Original) A permanently attached hose coupling, for a pressurized conduit
2 end, having a generally tubular nipple and a generally cylindrical shell permanently
3 attached to said nipple and generally surrounding said conduit end, said nipple having a
4 longitudinal axis, a first end, a second end, a plurality of circumferential grooves located
5 between said first and said second ends, a bore extending from said first end to said
6 second end, and an insert portion adjacent said plurality of grooves inserted into said
7 conduit end;

8 wherein said grooves are dimensioned for affixedly receiving at least one
9 of an inside surface, an end surface and an outside surface of said generally cylindrical
10 shell; and

11 said grooves comprising:
12 a first groove with a generally flat base portion parallel with said longitudinal axis, a first
13 substantially vertically oriented side wall, and a second substantially vertically oriented
14 side wall having a maximum radial extent less than said first side wall; and
15 second groove adjacent said first groove, with a generally flat base
16 portion parallel with said longitudinal axis having a diameter less than said first groove
17 base portion, a first substantially vertically oriented side wall having a maximum radial
18 extent similar to said first groove second side wall, and a second substantially vertically
19 oriented side wall having a maximum radial extent greater than said second groove first
20 side wall.

1 Claim 12 (Original) The hose coupling as in claim 11 wherein said insert portion has a
2 plurality of spaced, circumferentially extending, frusto-conically shaped protrusions on
3 the outer surface thereof.

1 Claim 13 (Original) The hose coupling as in claim 12 wherein one of said plurality of
2 spaced protrusions is positioned approximately equidistant between said second groove
3 and said second end and has a maximum radial extent greater than that of each of the

4 others of said plurality of protrusions.

1 Claim 14 (Original) The hose coupling as in claim 11 wherein said generally cylindrical
2 shell has a first end with an inwardly directed portion having an annular surface in an
3 abutting relationship with one of said plurality of circumferential grooves for said
4 permanent attachment.

1 Claim 15 (Original) The hose coupling as in claim 14 wherein said inwardly directed
2 portion is located at the longitudinal inner end of said generally cylindrical shell.

1 Claim 16 (Original) The hose coupling as in claim 14 wherein said inwardly directed
2 portion is located on the inside surface of said generally cylindrical shell.

1 Claim 17 (Original) The hose coupling as in claim 11 wherein said generally cylindrical
2 shell has a first end and a second end, said first end having a turned-in portion generally
3 directed towards said second end.

1 Claim 18 (Original) The hose coupling as in claim 17 wherein the outer surface of said
2 turned-in portion is in affixed abutment with said second groove first side wall.

1 Claim 19 (Original) The hose coupling as in claim 11 wherein the inside surface of said
2 generally cylindrical shell affixedly abuts said first and said second side walls of said
3 second groove.

Claims 20-26 (Cancelled)

1 Claim 27 (Original) A generally tubular nipple having a longitudinal axis, a first end, a
2 second end, an outer surface with a plurality of circumferential grooves, located between

3 said first and said second ends, for affixedly receiving a generally cylindrical shell, and a
4 bore extending from said first end to said second end;

5 wherein said plurality of circumferential grooves are dimensioned for
6 affixedly receiving at least one of an inside surface, an end surface and an outside surface
7 of said generally cylindrical shell; and

8 said plurality of grooves comprising:

9 a first groove with a generally flat base portion parallel with said
10 longitudinal axis, a first generally vertically oriented side wall, and a second generally
11 vertically oriented side wall having a maximum radial extent less than said first side wall;

12 a second groove adjacent said first groove, with a generally flat base
13 portion parallel with said longitudinal axis having a diameter less than said first groove
14 base portion, a first generally vertically oriented side wall having a maximum radial
15 extent substantially equal to said first groove second side wall, and a second generally
16 vertically oriented side wall having a maximum radial extent less than said second groove
17 first side wall; and

18 a third groove adjacent said second groove, with a generally flat base
19 portion parallel with said longitudinal axis having a diameter less than said second
20 groove base portion, a first generally vertically oriented side wall having a maximum
21 radial extent substantially equal to said second groove second side wall and a second
22 generally vertically oriented side wall having a maximum radial extent greater than said
23 third groove first side wall.

1 Claim 28 (Original) The generally tubular nipple as in claim 27 further including an
2 insert portion located between said third groove and said second end and has a plurality
3 of spaced, circumferentially extending, frusto-conically shaped protrusions on the outer
4 surface thereof.

1 Claim 29 (Original) The generally tubular nipple as in claim 27 wherein one of said
2 plurality of spaced protrusions is positioned approximately equidistant between said third
3 groove and said second end and has a maximum radial extent greater than that of each of
4 the others of said plurality of protrusions. 5

1
1 Claim 30 (Original) The generally tubular nipple as in claim 27 wherein said generally
2 flat base portion of each of said plurality of circumferential grooves has a series of
3 surface disruptions along its circumference.

1
1 Claim 31 (Original) The generally tubular nipple as in claim 27 wherein the outer
2 surface of said third groove second substantially vertically oriented side wall has threads
3 for attachment with said generally cylindrical shell.

1
1 Claim 32 (Original) A generally tubular nipple having a longitudinal axis, a first end, a
2 second end, an outer surface with at least two circumferential grooves located between
3 said first and said second ends for affixedly receiving a generally cylindrical shell, and a
4 bore extending from said first end to said second end;

5 wherein said at least two circumferential grooves are dimensioned for
6 affixedly receiving at least one of an inside surface, an end surface and an outside surface
7 of said generally cylindrical shell; and

8 said at least two circumferential grooves comprising:

9 a first groove with a generally flat base portion parallel with said
10 longitudinal axis, a first generally vertically oriented side wall, and a second generally
11 vertically oriented side wall having a maximum radial extent less than said first side wall;
12 and

13 second groove adjacent said first groove, with a generally flat base
14 portion parallel with said longitudinal axis having a diameter less than said first groove
15 base portion, a first generally oriented side wall having a maximum radial extent

16 generally equal to said first groove second side wall, and a second generally vertically
17 oriented side wall having a maximum radial extent greater than said second groove first
18 side wall.

1 Claim 33 (Original) The generally tubular nipple as in claim 32 further including an
2 insert portion located between said second groove and said second end and has a plurality
3 of spaced, circumferentially extending, frusto-conically shaped protrusions on the outer
4 surface thereof.

1 Claim 34 (Original) The generally tubular nipple as in claim 33 wherein one of said
2 plurality of spaced protrusions is positioned approximately equidistant between said
3 second groove and said second end and has a maximum radial extent greater than that of
4 each of the others of said plurality of protrusions.

1 Claim 35 (Original) The generally tubular nipple as in claim 32 wherein said generally
2 flat base portion of each of said at least two circumferential grooves has a series of
3 surface disruptions along its circumference.

1 Claim 36 (Original) The generally tubular nipple as in claim 32 wherein the outer
2 surface of said second groove second substantially vertically oriented side wall has
3 threads for attachment with said generally cylindrical shell.

Claims 37-42 (Cancelled) .

1 Claim 43 (Previously amended) A generally tubular nipple having a longitudinal axis, a
2 first end, a second end, an outer surface with a series of circumferential grooves located
3 between said first and second ends for affixedly receiving a generally cylindrical shell,
4 and a bore extending from said first end to said second end;

5 wherein said series of circumferential grooves are dimensioned for
6 affixedly receiving at least one of an inside surface, an end surface and an outside surface
7 of said generally cylindrical shell; and

8 said series of grooves comprising:

9 a first groove with a generally flat base portion parallel with said
10 longitudinal axis, a first substantially radially directed sidewall, and a second
11 substantially radially directed sidewall;

12 a second groove adjacent said first groove, with a generally flat base
13 portion parallel with said longitudinal axis having a diameter less than said first groove
14 base portion, a first substantially radially directed sidewall, having a maximum radial
15 extent generally equal to said first groove second sidewall, and a second substantially
16 radially directed sidewall; and

17 a third groove adjacent said second groove, with a generally flat base
18 portion parallel with said longitudinal axis having a diameter less than said second
19 groove base portion, a first substantially radially directed sidewall, having a maximum
20 radial extent generally equal to said second groove second sidewall, and a second
21 substantially radially directed sidewall having an outer surface with a series of threads for
22 attachment with said generally cylindrical shell.

Claim 44 (Cancelled)